

[Web](#) [Images](#) [Videos](#) [Maps](#) [News](#) [Shopping](#) [Gmail](#) [more ▼](#)
[Web History](#) | [Search settings](#) | [Sign in](#)


detecting status based on session control me

Search

Instant is off (show connections) ▼

About 594,000 results (0.63 seconds)

[Advanced search](#)**Everything**[Images](#)[Videos](#)[More](#)[Show search tools](#)**VoIP Protocols**

The Megaco protocol is used **between** elements of a physically decomposed multimedia gateway ... physical **device**, and a monolithic gateway such as described in H.246. .... During an RVP/IP **session**, only one class of RVP/IP **control message** are .... and RTP/UDP/IP to/from a Skinny Client or H.323 **terminal** for audio. ....

[www.protocols.com/pbook/VoIPFamily.htm](http://www.protocols.com/pbook/VoIPFamily.htm) - Cached · Similar

**[PDF] On-line service adaptation for mobile and fixed terminal devices**

File Format: PDF/Adobe Acrobat - Quick View  
by J Korva - Cited by 22 - Related articles

for both mobile and fixed **terminal devices**. The adaptation is done **based** on the .... There is no direct correspondence **between** source and target concepts, but it can be ... Internal services: generic services for **session control** and configuring user .... computer or subscribe to alarms of motion **detection** events, ...

[citeseerx.ist.psu.edu/viewdoc/download?doi=10.1.1.96.8514&rep...](http://citeseerx.ist.psu.edu/viewdoc/download?doi=10.1.1.96.8514&rep...)

**draft-ietf-opsawg-oam-overview-01**

For example, the emerging MPLS-TP OAM is in many ways **based** on [ITU-T Y.1731]. .... Delay Measurement DTE Data **Terminal** Equipment FDI Forward Defect Indication .... **Detect** Mult determines the number of missing BFD **Control** packets that ... and is used to measure delay and packet loss **between** the **session** endpoints. ...

<https://datatracker.ietf.org/doc/draft-ietf-opsawg-oam-overview/> · Cached

**Systems, Methods and Computer Program Products for Coordinated ...**

The method of claim 1, wherein **detecting** a network connectivity **status** of the UE .... These functions may be apportioned among several call **session control** ... The P-CSCF 130 may enable the registration of IP **terminals/devices** and the ... **between** the UE 210 and the NAF 230, which is secured **based** on the shared key ...

[www.feqs.org/patents/app/20090089425](http://www.feqs.org/patents/app/20090089425) - Cached

**Event ID 1019 — Terminal Server Communication**

Dec 4, 2009 ... Message: TS **Session** Broker failed to call **terminal** server %1 to rejoin. ... is not blocked **between** the TS **Session** Broker server and the **terminal** server. ... on your network allow Internet **Control Message** Protocol (ICMP) traffic. ... In **Device** Manager, check the **status** of the network adapter. ...

[technet.microsoft.com/en-us/library/cc727384\(WS.10\).aspx](http://technet.microsoft.com/en-us/library/cc727384(WS.10).aspx) · Cached · Similar

**Complete Protocol dictionary, glossary and reference - I ...**

Interne **Control Message** Protocol (ICMP) is an integrated part of the IP suite. ... iFCP uses TCP to provide congestion control, error **detection** and recovery. .... for establishing and managing connections **between** IP-**based** storage **devices**, ... to control a **terminal** with screen and keyboard and similar **devices**, ...

[www.networkdictionary.com/protocols/i.php](http://www.networkdictionary.com/protocols/i.php) - Cached · Similar

[Terminal Characteristics - OpenVMS documentation](#)

Device unit number to identify the **terminal** that sent the **message**.

... (Pressing a key other than Return might **detect** the wrong baud rate; if this occurs, ... selects the frame size (the number of data bits that the **device** can transmit) **based** on how .... See Section 5.2.3.1 for information on modem signal **control**. ...

h71000.www7.hp.com/doc/73final/6136/6136pro\_017.html - Cached

[PDF] [Documentation: Kaleidescape System Control Protocol Reference Manual](#)

File Format: PDF/Adobe Acrobat - Quick View

The Kaleidescape System uses a simple text-**based control** .... In the **terminal session** window you should also see this:

01/1/000:/89 ..... external scalers or display **devices** that do not automatically **detect** changes in the video .... standby mode when this **message** is received, only the normal **status** reply is sent. ...

www.kaleidescape.com/.../Kaleidescape-System-Control-Protocol-Reference-Manual.pdf

[CCNA Questions and Answers](#)

**Based** upon the graphic, which **device** type best describes the function of wireless **device** "Cell A"? .... Host1 has sent a SYN **message** to begin **session** establishment. .... provide media access **control** support frame **error** **detection** carry routing .... What type of network cable is used **between** a **terminal** and a console ...

www.scribd.com/doc/.../CCNA-Questions-and-Answers - Cached - Similar

[PDF] [TR-122](#)

File Format: PDF/Adobe Acrobat - Quick View

**Base** Requirements for Consumer-Oriented Analog **Terminal** Adapter. Functionality. 1 Purpose .... [13] IETF RFC 792 (September 1981), Internet **Control Message** Protocol. .... **Terminal** Equipment - Stutter Dial Tone **Detection** **Device** Performance ... Indication Event Package for the **Session** Initiation Protocol (SIP). ...

www.broadband-forum.org/technical/download/TR-122v1.01.pdf - Similar

1 2 3 4 5 6 7 8 9 10

[Next](#)

[Search Help](#)

[Give us feedback](#)

[Google Home](#)

[Advertising Programs](#)

[Business Solutions](#)

[Privacy](#)

[About Google](#)